

JI-CT-156

DUAL-SCREEN CONFERENCE TERMINAL

Desktop delegate terminal — 15.6-inch touch display, 10.1-inch rear screen, gooseneck microphone and optional embedded PC.

DUAL SCREEN

15.6" + 10.1"

10-POINT TOUCH

GOOSENECK MIC

EMBEDDED PC



FRONT · SIDE · DEPLOYED

GOOSENECK MICROPHONE · WINDOWS WORKSTATION

01 OVERVIEW

The **Jistron JI-CT-156** is a desktop conference terminal for paperless meetings and discussion systems. A 15.6-inch Full HD capacitive touch screen faces the delegate, while a 10.1-inch screen on the reverse presents to the participant opposite. An integrated gooseneck microphone provides voice pickup for discussion, and a built-in loudspeaker handles local audio. An optional embedded PC (Intel Core i5, Windows 10) turns the unit into a self-contained workstation. The anodised aluminium-alloy chassis is available in four finishes and sits directly on the conference table.

02 KEY FEATURES

- **Dual-screen terminal**
15.6-inch Full HD touch screen for the delegate; 10.1-inch rear screen for the participant opposite.
- **Integrated gooseneck microphone**
Flexible gooseneck microphone for clear voice pickup during discussion.
- **Built-in loudspeaker**
Loudspeaker built into the chassis for local audio playback.
- **CNC aluminium-alloy body**
Anodised chassis — brushed black, brushed silver, matte black or sparkle silver.
- **Ten-point capacitive touch**
Front screen only (single-side touch); projected-capacitive, ten simultaneous points.
- **Optional embedded PC**
Intel Core i5-4200U, 4 GB RAM, 64 GB storage, Windows 10 — customisable.
- **Full HD front · HD rear**
1920 × 1080 front display, 1366 × 768 rear display, 16 : 9.
- **Compact desktop chassis**
420 × 190 × 237.5 mm, with a tilted screen for comfortable desktop viewing.

03 APPLICATIONS

Boardrooms	Council Chambers	Courtrooms	Command & Control Rooms	Lecture Theatres
Hotels & Convention Venues				

04 TECHNICAL SPECIFICATIONS

DISPLAYS	
Front display	15.6 inch · 1920 × 1080 (Full HD) · 16 : 9
Front touch	Capacitive ten-point multi-touch · single-side (front only)
Rear display	10.1 inch · 1366 × 768 · non-touch
Brightness	220 cd/m ²
Contrast ratio	Front 500 : 1 · Rear 800 : 1
Viewing angles	45° / 45° / 20° / 40° (typ., CR ≥ 10)
MICROPHONE & AUDIO	
Microphone	Integrated gooseneck microphone
Loudspeaker	Built-in loudspeaker
EMBEDDED PC – OPTIONAL	
Processor	Intel Core i5-4200U
Memory	4 GB
Storage	64 GB (optional · customisable)
Operating system	Windows 10 (64-bit)
POWER & PHYSICAL	
Power supply	AC 220 V · 50/60 Hz
Power consumption	25 W
Dimensions	420 × 190 × 237.5 mm
Construction	Aluminium alloy, CNC-machined · anodised
Finishes	Brushed black · brushed silver · matte black · sparkle silver

Jistron

AUDIO VISUAL EQUIPMENT · TALLINN, ESTONIA

05 ORDERING INFORMATION

MODEL	DESCRIPTION	NOTES
JI-CT-156	Dual-screen conference terminal, 15.6" FHD touch + 10.1" rear, gooseneck microphone	Embedded PC optional · specify surface finish at order

Specifications on this datasheet refer to the JI-CT-156. Embedded-PC configuration and custom anodised finishes are available on request.

06 ABOUT JISTRON

Jistron is a European audio–visual brand headquartered in Tallinn, Estonia. It supplies motorised conference lifts, microphone systems and installed audio–visual solutions for boardrooms, chambers and lecture environments; products are manufactured at audited partner facilities.

ADDRESS PÄRNU MNT 142, 11317 TALLINN, ESTONIA · EMAIL [INFO@JISTRON.COM](mailto:info@jistron.com) · WEB [JISTRON.COM](http://jistron.com)