

J I - M U H 0 8 0 8 S - P R O

8x8 SEAMLESS MATRIX SWITCHER

Professional HDMI 8x8 seamless matrix switcher with 4K30 support, analog audio de-embedding, EDID management and TCP/IP / RS-232 control.

8x8 HDMI	SEAMLESS	4K@30Hz	HDMI 1.4	TCP/IP	RS-232
----------	----------	---------	----------	--------	--------



01 OVERVIEW

The JiStron JI-MUH0808S-Pro is a professional 8x8 seamless HDMI matrix switcher with eight HDMI inputs and eight HDMI outputs. It supports HDMI 1.4 video up to 3840 x 2160 at 30 Hz with RGB/YCbCr color spaces, and provides eight analog audio outputs for HDMI audio de-embedding. The system also provides comprehensive EDID management together with front-panel, RS-232 and TCP/IP control for professional AV routing applications.

02 KEY FEATURES

- **8x8 HDMI matrix**

Eight HDMI inputs can be independently routed to eight HDMI outputs.
- **Seamless switching**

Designed for seamless source switching between routed outputs.
- **4K video support**

Supports HDMI 1.4 resolutions up to 3840 x 2160 at 30 Hz.
- **Analog audio de-embedding**

Eight 3.5 mm analog audio outputs support HDMI audio de-embedding.
- **EDID management**

Seven built-in EDIDs plus custom EDID and output-EDID learning are supported.
- **Multiple output resolutions**

Twelve selectable output resolutions are available.
- **CEC support**

The first input and first output channels support CEC control.
- **Flexible control**

Front panel, RS-232 and TCP/IP client control are supported.

03 ROUTING, EDID & CONTROL

SCENES	EDID	CEC	AUDIO	TCP/IP	RS-232
--------	------	-----	-------	--------	--------

04 MATRIX OPERATION & SYSTEM FUNCTIONS

1 FRONT-PANEL ROUTING

Illuminated input/output keys and LCD provide local matrix routing and status operation.

3 PRESET SCENES

Routing configurations can be stored and recalled as preset scenes.

5 EDID MANAGEMENT

Built-in, custom and learned output EDID data can be assigned to inputs.

7 OUTPUT SETTINGS

Client software supports output resolution, signal format, brightness, contrast and analog-audio settings.

2 TCP/IP CLIENT CONTROL

RJ45 network control supports the supplied client software and IP-based system management.

4 RS-232 CONTROL

Bi-directional RS-232 is provided for external control and peripheral integration.

6 AUDIO / VIDEO SEPARATION

The source documentation specifies independent analog audio de-embedding for eight output channels.

8 STANDBY & LOCK

Standby mode and front-panel button lock/unlock functions are supported.

05 VIDEO PERFORMANCE & INTEGRATION

■ 4K30 compatibility

Supports HDMI 1.4 and video resolutions up to 3840 x 2160 at 30 Hz with 4:4:4 color sampling.

■ HDMI / DVI compatibility

Inputs are compatible with HDMI and DVI source formats as specified in the manual.

■ Continuous hot plugging

The manual specifies continuous hot plugging support for HDMI ports.

■ Power-off memory

Routing and system status can be retained through the documented power-off memory function.

06 TECHNICAL SPECIFICATIONS

VIDEO	
HDMI inputs	8 x HDMI
Input connectors	8 x HDMI Type-A female
Input resolution	Up to 4K@30Hz 4:4:4
HDMI outputs	8 x HDMI
Output connectors	8 x HDMI Type-A female
Output resolution	Up to 4K@30Hz 4:4:4
HDMI version	HDMI 1.4
HDCP version	HDCP 1.3

ANALOG AUDIO OUTPUT	
Audio outputs	8 x analog audio
Output connectors	8 x 3.5 mm audio jack
Audio format	PCM

CONTROL	
Control	1 x RS-232 IN · 2 x RS-232 OUT · 1 x TCP/IP · 14 front-panel buttons
Control ports	1 x DB9 female · 1 x DB9 male · 2 x RJ45 · 22 illuminated buttons

06 TECHNICAL SPECIFICATIONS - CONTINUED

GENERAL	
Transmission distance	4K 30 Hz: <= 5 m · 1080p: < 15 m
Operating temperature	0 °C to +40 °C
Storage temperature	-10 °C to +50 °C
Relative humidity	10% - 90%
External power supply	DC 12 V, 2 A
Dimensions (W x H x D)	483 x 44 x 236 mm
Net weight	3 kg

SYSTEM FEATURES	
Seamless switching	Supported
Output resolutions	12 selectable resolutions
EDID	7 built-in + custom + output-EDID learning
CEC	Supported on first input and first output
Power-off memory	Supported
Standby mode	Supported

07 ORDERING INFORMATION

MODEL	DESCRIPTION	NOTES
J1-MUH0808S-Pro	8x8 Seamless HDMI Matrix Switcher with 4K30, analog audio de-embedding, EDID, TCP/IP and RS-232 control	8 HDMI IN / 8 HDMI OUT

Technical specifications and key functions for the J1-MUH0808S-Pro are presented here for system design, tendering and product selection.

08 ABOUT JISTRON

Jistron is a European audio-visual brand headquartered in Tallinn, Estonia. It supplies conference systems, signal management and installed audio-visual solutions for boardrooms, chambers and command environments; products are manufactured at audited partner facilities.