


J I 1 2 0 T - H

WIRELESS BODYPACK TRANSMITTER WITH HEADSET MICROPHONE

Wireless IoT bodypack transmitter supplied with a headset microphone for speeches, performances and interviews.

BODYPACK	HEADSET MIC	DIGITAL RF	2200 mAh	15 H TALK
----------	-------------	------------	----------	-----------



01 OVERVIEW

The Jistron JI120T-H is a wireless IoT bodypack transmitter intended for speeches, performances and interviews and can be used with a headset microphone or a lavalier microphone. It uses digital wireless RF transmission technology for audio and control-management data, with strong anti-interference performance, an approximately 1-inch color display, and a built-in lithium battery for up to 15 hours of speaking time.

02 KEY FEATURES

- **Wireless IoT bodypack design**

Suitable for speeches, performances and interviews.
- **Headset or lavalier use**

Can be used with a lavalier microphone or a headset microphone.
- **Color status display**

Approx. 1-inch high-definition true color screen shows battery, signal, microphone status, channel and ID number.
- **Low-power battery design**

Built-in high-capacity lithium battery with up to 15 hours of speaking time and 40 hours standby.
- **Digital RF transmission**

Audio signals and control-management data are transmitted via digital wireless RF.
- **Camera tracking support**

Supports automatic camera tracking with a compatible camera tracking host and PC preset.
- **Dedicated charging dock**

Comes with a dedicated charging dock for easy charging.
- **Network audio support**

When used with the main unit, network audio transmission allows interconnected audio signal streaming.

03 DISPLAY & SYSTEM FUNCTIONS

BATTERY	SIGNAL	MIC STATUS	CHANNEL	ID NUMBER	CAM TRACK
---------	--------	------------	---------	-----------	-----------

04 WIRELESS OPERATION & INTEGRATION

1 DISPLAY INFORMATION

The screen displays battery level, signal strength, microphone status, channel and ID number.

3 HEADSET / LAVALIER USE

The transmitter supports use with a headset microphone or a lavalier microphone.

5 CAMERA TRACKING

Supports automatic camera tracking with a compatible tracking host and PC preset.

7 CHARGING DOCK

A dedicated charging dock is supplied for convenient charging.

2 DIGITAL RF TRANSMISSION

Digital wireless RF technology is used for transmitting audio signals and control-management data.

4 NETWORK AUDIO

With the main unit, network audio transmission supports interconnected audio signal streaming.

6 AUTOMATIC UNIT ID

Each conference unit has a unique serial number, and the system can automatically assign IDs.

8 STABLE PERFORMANCE

The source specifies strong anti-interference capability and stable wireless performance.

05 SYSTEM INTEGRATION & OPERATION

■ Main-unit interoperability

When used with the main unit, the transmitter supports network audio transmission for interconnected streaming.

■ Camera preset workflow

Automatic camera tracking is available with a compatible camera tracking host and PC preset configuration.

■ Automatic ID assignment

Unique serial numbering allows the conference system to automatically assign device IDs.

■ Convenient charging

The dedicated charging dock provides an easy routine for daily charging and deployment.

06 TECHNICAL SPECIFICATIONS

RF & TRANSMISSION	
Product type	Wireless bodypack transmitter with headset microphone
Harmonic radiation	< -65 dBm
Frequency bandwidth	50 MHz
Max frequency deviation	+/- 45 kHz
RF power output	15 mW
Wireless technology	Digital wireless RF for audio and control-management data
DISPLAY & CONTROL	
Display	Approximately 1-inch high-definition true color screen
Display information	Battery level · signal strength · microphone status · channel · ID number
Accessory microphone types	Headset microphone or lavalier microphone
Camera tracking	Supported with camera tracking host and PC preset
Unit identification	Unique serial number; conference system can automatically assign IDs

06 TECHNICAL SPECIFICATIONS - CONTINUED

POWER & PHYSICAL	
Battery type	Built-in high-capacity lithium battery
Battery capacity	2200 mAh
Speaking time	15 hours
Standby time	40 hours
Dimensions	L x W x H = 102 x 68 x 22 mm
Weight	0.12 kg

ACCESSORIES & OPERATION	
Charging accessory	Dedicated charging dock
Network audio	Available when used with the main unit for interconnected audio signal streaming
Suitable applications	Speeches · performances · interviews

07 ORDERING INFORMATION

MODEL	DESCRIPTION	NOTES
J1120T-H	Wireless bodypack transmitter with headset microphone - color display, digital RF and camera tracking support	2200 mAh battery; dedicated charging dock

Specifications on this datasheet refer to the J1120T-H wireless bodypack transmitter. Main unit and related conference components are specified separately as required.

08 ABOUT JISTRON

Jistron is a European audio-visual brand headquartered in Tallinn, Estonia. It supplies conference systems, audio processors and installed audio-visual solutions for boardrooms, chambers and command environments; products are manufactured at audited partner facilities.

ADDRESS PÄRNU MNT 142, 11317 TALLINN, ESTONIA · EMAIL INFO@JISTRON.COM · WEB JISTRON.COM

The specifications are subject to change without prior notice.

Copyright © Jistron. All rights reserved.