

J I 1 6 4 C

NETWORK CHARGING DOCK

Four-unit network charging dock for compatible charging boundary microphones and tabletop gooseneck microphones.

4-UNIT	CONTACT DOCK	4 H FULL	PC SOFTWARE	NETWORK
--------	--------------	----------	-------------	---------



01 OVERVIEW

The Jistron JI164C is a network charging dock designed for compatible charging boundary microphones and tabletop gooseneck microphones. The dock provides four charging positions with contact-based charging and fully charges connected units in approximately 4 hours. Charging level can be monitored through PC software over the network for convenient system management.

02 KEY FEATURES

- **Four-unit charging dock**
Four compatible microphone units can be charged together in one dock.
- **Contact-based charging**
The dock uses contact charging for guided and stable placement.
- **Full charge in 4 hours**
Connected units are fully charged in approximately 4 hours.
- **Boundary microphone support**
Compatible with charging boundary microphones.
- **Network software monitoring**
Charging level can be monitored through PC software over the network.
- **Gooseneck microphone support**
Compatible with tabletop gooseneck microphones.
- **Centralized desk charging**
The four-position design simplifies charging and storage on the meeting table or charging area.
- **Managed charging workflow**
A single dock supports organized charging for multiple compatible conference units.

03 CHARGING & NETWORK FUNCTIONS

4-UNIT CHARGE	CONTACT DOCK	PC SOFTWARE	NETWORK	MIC COMPATIBLE
---------------	--------------	-------------	---------	----------------

04 CHARGING OPERATION & COMPATIBILITY

1 FOUR CHARGING POSITIONS

The dock supports simultaneous charging for up to four compatible units.

3 FULL-CHARGE PERFORMANCE

A complete charging cycle takes approximately 4 hours.

5 BOUNDARY MIC COMPATIBILITY

Supports compatible charging boundary microphones.

7 CENTRALIZED CHARGING LAYOUT

The charger groups multiple units in one organized charging position.

2 CONTACT-BASED DOCKING

The charging dock uses contact charging for direct placement of the units.

4 SOFTWARE MONITORING

Charging level can be monitored via PC software over the network.

6 GOOSENECK MIC COMPATIBILITY

Supports compatible tabletop gooseneck microphones.

8 NETWORK-BASED MANAGEMENT

The charger can be supervised from the PC software through the network connection.

05 SYSTEM DEPLOYMENT & MONITORING

■ Shared charging platform

A single four-position dock simplifies charging management for multiple compatible conference units.

■ Network-visible charging level

Charging level information can be checked through PC software over the network.

■ Mixed compatible microphone support

The dock is intended for compatible charging boundary microphones and tabletop gooseneck microphones.

■ Fast replenishment

Approximate 4-hour full charging supports daily conference-system preparation.

06 TECHNICAL SPECIFICATIONS

SYSTEM & CHARGING	
System type	Network charging dock
Charging configuration	4-unit charger
Charging method	Contact-based charging dock
Full-charge time	Approximately 4 hours
Application	Charging dock for compatible conference microphone units
MONITORING & CONTROL	
Charging status monitoring	Charging level can be monitored via PC software over the network
Monitoring path	Network-based PC software
COMPATIBILITY	
Compatible microphone type 1	Charging boundary microphones
Compatible microphone type 2	Tabletop gooseneck microphones

06 TECHNICAL SPECIFICATIONS - CONTINUED

PRODUCT SUMMARY	
Model	J1164C
Product description	Network charging dock for compatible charging boundary microphones and tabletop gooseneck microphones
Charging positions	4
Charge completion	Approximately 4 hours
Monitoring method	Charging level monitoring through PC software over the network

07 ORDERING INFORMATION

MODEL	DESCRIPTION	NOTES
J1164C	Network charging dock - 4-unit contact-based charging for compatible conference microphone units	Charging level monitoring via PC software over the network

Specifications on this datasheet refer to the J1164C network charging dock. Compatible microphone units are specified separately as required.

08 ABOUT JISTRON

Jistron is a European audio-visual brand headquartered in Tallinn, Estonia. It supplies conference systems, audio processors and installed audio-visual solutions for boardrooms, chambers and command environments; products are manufactured at audited partner facilities.

ADDRESS PÄRNU MNT 142, 11317 TALLINN, ESTONIA · EMAIL [INFO@JISTRON.COM](mailto:info@jistron.com) · WEB [JISTRON.COM](http://jistron.com)

The specifications are subject to change without prior notice.

Copyright © Jistron. All rights reserved.