

J I 2 0 D - E

DIGITAL NETWORK WIRED DELEGATE UNIT

Gooseneck delegate microphone with fully digital audio, VIP assignment and CAT6E connectivity.

DELEGATE	CAT6E	5 SPEECH MODES	40 HZ-20 KHZ	DC24V
----------	-------	----------------	--------------	-------



01 OVERVIEW

The Jistron JI20D-E is a digital network wired delegate unit with a gooseneck microphone for conference systems. It combines fully digital audio processing with a high-performance CPU, a special electret condenser microphone core, CAT6E network connectivity and optional digital-analog dual backup. The unit supports ring hand-in-hand connection, hot-plug operation, camera tracking, five speaking modes, configurable voice wake-up and VIP unit assignment.

02 KEY FEATURES

- **Fully digital audio**
Built-in high-performance CPU provides fast processing and improved conference audio quality.
- **VIP unit assignment**
The delegate unit can be configured as a VIP unit and is not limited by the opening mode.
- **Ring connection reliability**
Failure or replacement of one microphone does not interrupt other units in the system.
- **Digital-analog backup**
Customizable dual-backup operation supports stable and uninterrupted meetings.
- **Five speech modes**
Normal, FIFO, Free, Application and Voice Wake-up modes are supported.
- **Camera tracking support**
Works with a camera tracking host after computer preset configuration.
- **Voice wake-up control**
Startup sensitivity and automatic shutoff time in silent mode can be configured.
- **Anti-interference microphone**
Electret condenser microphone core is designed for high sensitivity and stable operation.

03 OPERATIONAL FUNCTIONS

Hot Plug	Trigger / Hold	Auto Unit ID	3.5 mm Headphone	Hidden Cable Exit	LED Indicator
----------	----------------	--------------	------------------	-------------------	---------------

04 CONTROLS & INTEGRATION

1 VIP UNIT MODE

The delegate unit can be set as a VIP unit and is not limited by the microphone opening mode.

3 MICROPHONE SWITCHING

Supports trigger switching or press-and-hold to open and release to switch.

5 CABLE ROUTING

The included 1.8 m CAT6E cable can exit through the hidden bottom outlet or from the rear.

7 HOT PLUG

Microphones can be added to the connected system at any time.

2 CAMERA TRACKING

The unit supports automatic camera tracking when used with a camera tracking host and computer presets.

4 VOICE WAKE-UP

Startup sensitivity can be set and the microphone can automatically switch off after a configured silent period.

6 HEADPHONE CONNECTION

One 3.5 mm stereo headphone jack is provided for connecting headphones.

8 AUTOMATIC IDENTIFICATION

Each conference unit has a unique serial number and the system can automatically assign its ID.

05 SYSTEM RELIABILITY & INDICATORS

■ Ring hand-in-hand connection

A failure or replacement of a single microphone does not affect other extensions; a connection failure between microphones does not stop system operation.

■ Digital-analog dual backup

A customizable digital-analog dual backup function is available to support stable and reliable meeting operation.

■ Two-color status indicator

The unit uses a two-color LED indicator; red indicates speaking.

■ Anti-mobile-phone interference

The microphone core is designed for stable, durable and reliable operation in the presence of mobile-phone interference.

06 TECHNICAL SPECIFICATIONS

SYSTEM & CONTROL	
System type	Digital network wired delegate unit (gooseneck)
Delegate function	Can be set as a VIP unit; not limited by opening mode
Speech modes	Normal · First-in-first-out (FIFO) · Free · Application · Voice Wake-up
Microphone opening modes	Trigger switch · Long press to open / release to switch
Hot-plug support	Supported; microphones can be added to the system while connected
Connection topology	Ring hand-in-hand connection technology
Backup function	Customizable digital-analog dual backup
Camera tracking	Supported with camera tracking host and computer presets
MICROPHONE & AUDIO	
Microphone core	Special electret condenser microphone core
Directional characteristics	Cardioid
Microphone type	Cardioid condenser
Frequency response	40 Hz - 20 kHz
Sensitivity	-32 dBV
Distortion	< 1%
CONTROL & INDICATION	
Switch mode	Physical switch
Speaking indicator	Two-color LED indicator; red indicates speaking
Unit identification	Unique serial number; conference system can automatically assign an ID

06 TECHNICAL SPECIFICATIONS - CONTINUED

NETWORK & CONNECTIVITY	
Connection method	CAT6E network cable
Included network cable	1.8 m Category 6e network cable
Headphone connection	1 × Ø3.5 mm stereo headphone jack
Cable outlet	Hidden bottom outlet or rear cable exit
POWER & PHYSICAL	
Power supply	DC24V host power supply
Power consumption	1.5 W
Base dimensions	180 × 142 × 59 mm
Gooseneck length	415 mm
Weight	810 g

07 ORDERING INFORMATION

MODEL	DESCRIPTION	NOTES
J120D-E	Digital network wired delegate unit - gooseneck, CAT6E, VIP assignment	Includes 1.8 m Category 6e network cable

Specifications on this datasheet refer to the J120D-E delegate unit. System hosts and related conference components are specified separately as required.

08 ABOUT JISTRON

Jistron is a European audio-visual brand headquartered in Tallinn, Estonia. It supplies conference systems, audio processors and installed audio-visual solutions for boardrooms, chambers and command environments; products are manufactured at audited partner facilities.

ADDRESS PÄRNU MNT 142, 11317 TALLINN, ESTONIA · EMAIL INFO@JISTRON.COM · WEB JISTRON.COM

The specifications are subject to change without prior notice.
Copyright © Jistron. All rights reserved.